

(12) UK Patent Application (19) GB (11) 2 299 478 (13) A

(43) Date of A Publication 02.10.1996

(21) Application No 9603415.2

(22) Date of Filing 19.02.1996

(30) Priority Data

(31) 9506551

(32) 30.03.1995

(33) GB

(71) Applicant(s)

Sony United Kingdom Limited

(Incorporated in the United Kingdom)

The Heights, Brooklands, WEYBRIDGE, Surrey,
KT13 0XW, United Kingdom

(72) Inventor(s)

Richard John Bush

Robert Alexander

(74) Agent and/or Address for Service

J A Kemp & Co

14 South Square, Gray's Inn, LONDON, WC1R 5LX,
United Kingdom

(51) INT CL⁶

H04N 9/77

(52) UK CL (Edition O)

H4F FD12X FD2B FD30J FD30K FGB

(56) Documents Cited

GB 2121645 A WO 87/06419 A US 4803548 A

(58) Field of Search

UK CL (Edition O) H4F FGB FGC FGT FHHX FHL FHM

INT CL⁶ H04N 5/243 9/64 9/68 9/77

Online: WPI

(54) Video filming scene correction

(57) A method of filming a scene with a video camera whereby the brightness and/or colour of at least one selected area of a video image is adjusted by processing 20 the video image data representing the video image prior to the video amplifier stage of the video camera. There is also provided a video apparatus having a processing means connected between the imaging device and the video amplifier and processor of a video camera.




Fig.5.

GB 2 299 478 A




Fig.1.

Fig.2.






Fig.3.









Fig.5.

VIDEO FILMING METHOD AND APPARATUS

The present invention relates to a video filming method and apparatus. It has particular use in the filming
5 of a non-uniformly lit scene, such as one lit by a variety of light sources of different intensities or colour temperatures or such as one where certain parts of the scene are shielded from one or more of those light sources.

In any scene, there may well be different sources of
10 light, each contributing its own colourisation and intensity to the various areas of the scene. This is true especially of scenes outside the controlled environment of a TV studio.

Typically, the chain of filming equipment comprising cameras, processors, etc is set up to handle only the most
15 critical area of a scene. This has the result that the displayed image may contain colour casts and shading, "burnt-out" areas of highlights, areas of lost detail, etc.

These problems may arise outside, for instance, as a result of bright sunshine, or inside, as illustrated in
20 Figure 1 of the accompanying drawings.

Figure 1 illustrates a typical indoor scene. The scene is illuminated by a combination of light sources including daylight, fluorescent tubes and tungsten lamps. Shadows are cast by these mixed sources, resulting in areas
25 of the scene being illuminated to different proportions by the various light sources.

With the illustrated scene, some areas will be

illuminated by the high intensity daylight source and others by the lower intensity artificial lamps. This will result in a range of luminance which would be too great to be rendered correctly by a TV camera and system. Furthermore, illumination by daylight will be blue for a camera set for the 3200°K colour temperature of studio cast and lighting. Similarly, illumination by the fluorescent tubes will influence the colour of the image, since they have a line spectrum output in the range of 2900°K to 8900°K.

10 Previously, as illustrated in Figure 2 of the accompanying drawings, these problems have been dealt with by the use of additional corrective lighting, together with colour and neutral density filters. By correcting the variable light levels and colour temperatures of the mixed sources, a scene may be produced which, when viewed through the television system, will give an acceptable result. In particular, neutral density filters may be placed over the windows to reduce the luminance level of the daylight source, colour correcting filters may be placed over the windows and fluorescent tubes to match the desired colour temperature (fluorescent tubes tend to cause a magenta colour cast), bulbs may be replaced with colour corrected types and, finally, additional lighting may be added to reduce the loss of detail in shadows.

25 This known method tends to reduce the ambient feel of a set or location. It is also costly as a result of the wide selection of filters required and the significant time

needed to set up a correctly balanced scene. Furthermore,
this method is not well adapted to reacting to changes in
the scene, eg. resulting from panning of the camera across
the scene or daylight changing with time of day or weather
5 conditions.

Hence, it is an object of the present invention to
provide an improved system of filming such scenes.

According to the present invention there is provided a
method of filming with a video camera having an imaging
10 device for producing video image data representing the video
image and a video amplifier stage the method comprising:

adjusting the brightness and/or colour of at least
one selected area of the video image by processing the video
image data prior to its processing by the video amplifier
15 stage of the video camera.

According to the present invention there is also
provided a video apparatus comprising:

a video camera having an imaging device for producing
video image data representing a video image;
20 selection means for enabling an operator to designate
a selected area of the video image and enter information
regarding the brightness and/or colour of the selected area;
processing means connected to the imaging device and
the selection means for processing the video image data of
25 the selected area so as to adjust the brightness and/or
colour of the selected area according to the entered
information; and

a video amplifier and processor connected to the output of the processing means.

According to the present invention, there is also provided a video camera device for use with a video camera, 5 having an imaging device for producing video image data representing a video image and having a video amplifier and processor, the device being adapted for insertion into the camera and being arranged for connection to the output of the imaging device and the input of the video amplifier and 10 processor, the device comprising:

processing means for processing video image data of a selected area of the video image so as to adjust the brightness and/or colour of the selected area.

Thus, with the present invention, the need to change a 15 scene by introducing filters, changing light sources and introducing new light sources is not necessary. By processing the video image signal, it is possible to allow selective correction by an operator of luminance and chrominance aberrations within the scene so as to render the 20 image acceptable.

Furthermore, by doing this processing directly after the video image data is produced by the imaging device and before any restrictions on its dynamic range are imposed by the video amplifier and processor, loss of detail, which 25 would occur if processing was carried out at a later stage, is avoided.

The present invention will be more clearly understood

from the following description given by way of example only,
with reference to the accompanying drawings in which:

Figure 1 illustrates a typical scene having mixed
light sources;

5 Figure 2 illustrates the corrective measures taken
according to the prior art;

Figure 3 illustrates an overall system embodying the
present invention;

Figure 4 illustrates an embodiment of the present
10 invention; and

Figure 5 illustrates an embodiment of the present
invention in a video camera.

Figure 3 illustrates schematically a system including
a signal processing unit 2 embodying the present invention.

15 The signal processing unit 2 receives a video signal from an
imaging device 1 and is controlled by any suitable control
panel 7 including, for instance, keys, a joystick, a tracker
ball or a mouse.

In the system of Figure 3, the signal processing unit
20 2 is connected to recording devices 3 and 4 so as to record
both processed and unprocessed signals. Furthermore, it is
connected to a display device 5 and a measurement display
device 6, for displaying respectively the image signal and a
measurement signal. However, in a preferred embodiment of
25 the present invention as illustrated in Figure 5, the signal
processing unit 20 is supplied with a video signal from the
imaging device 1 of the video camera and passes its output

back to the video amplifier of the video camera.

Preferably, it comprises an additional circuit board for insertion into the video camera itself. In this way, the signal processing unit makes use of the output processing of
5 the video camera, such that the video camera may be connected to recording devices and display devices in a normal way.

The signal processing unit 2 will now be described with additional reference to Figure 4.

10 The video signal input to the signal processing unit 20 is input to the metering and movement detection unit 21. As illustrated, the unprocessed signal is also sent on in parallel, for instance to the video amplifier of Figure 5 without further processing. However, a switch may be used
15 to selectively supply or by-pass the signal processing unit 20.

The metering and movement detection unit 21 supplies information regarding the video image to a control and computation unit 25. In the preferred embodiment, the video
20 image is processed as red, green and blue components. Thus, as illustrated in Figure 4, the metering and movement detection unit 21 is connected to the RGB frame store 22 for supplying the red, green and blue components to the RGB frame store 22.

25 The RGB frame store 22 is controlled by the control and computation unit 25 and supplies the red, green and blue components of the video image to a multiplier 23 which is

also under the control of the control and computation unit 25. In this way, the control and computation unit 25 can individually cause portions of the red, green and blue components of a video image to be scaled such that the
5 luminance and chrominance of the video image may be adjusted on a pixel by pixel basis.

The multiplier 23 supplies the red, green and blue components to an output conditioning unit 24 which may include additional video processing and a feed back to the
10 control and computation unit 25 to ensure correct processing.

The output conditioning unit 24 then supplies the processed signal for further processing, for instance as illustrated in Figure 5, and then recording.

15 An output of the conditioning unit 24 is also supplied, via an adder 28, to the display device 5. The adder is used to combine text, cursor and window information with the process signal output. The text, cursor and window information is generated by a text, cursor and window
20 generator 27 under the control of the control and computation unit 25. It causes the video image to be displayed together with text, cursors, outlining, etc.

Preferably, a memory 26 is connected to the control and computation unit 25 so that information regarding
25 correction of the various areas of the video image may be stored.

In operation, the control panel 7 is used in

conjunction with the control and computation unit 25, the text, cursor and window generator 27 and the adder 28 to identify and select areas of concern on the display device 5. This is most simply achieved by the operator moving a
5 cursor on the display device so as to draw a line outlining those areas.

Preferably, the control and computation unit 25 then operates in conjunction with the metering and movement detection unit 21 to search for colour or brightness
10 transitions in the vicinity of the boundary marked out on the display device 5. In this way, the operator need only approximately identify the areas requiring adjustment for the control and computation unit 25 to establish the precise boundaries.

15 Once an area has been selected in this way, the control and computation unit 25 may establish from the metering and movement detection unit 21, the brightness and colour temperature of the light source. For the convenience of the operation, these values may be displayed on
20 measurement display device 6 in the Figure 3 embodiment or included as text with the video image in the Figure 4 embodiment. Furthermore, if necessary, these values may be stored in memory 26, together with information regarding position of the selected area in question.

25 On the basis of the colouring and brightness of the selected areas of the image on the display device and/or the measured colour temperatures and brightness, the operator

may then adjust the image as required. For instance, a selected area which is too bright may have the brightness of its pixels reduced so as to prevent subsequent clipping and loss of detail. Thus, according to the input from the
5 control panel 7, the control and computation unit 25 may calculate the required multiplication factors for the red, green and blue components so that the multiplier 23 may apply those factors to pixels within the selected area.

It is preferable that the device employs some fuzzy
10 logic so that, particularly where there is no sharp transition between areas of differing illumination, the correction factors are applied to the video image so as to give a smooth transition in the image.

Once the areas have all been selected in this way, the
15 control and computation unit 25 operates in conjunction with the metering and movement detection unit 21 and memory 26 so that as areas of the image move, the correction factors stored in the memory 26 may be applied to the pixels corresponding to the selected area in its new position.

20 The memory may store data for an entire scene such that it may be recalled at some later date when a similar scene is being filmed.

Preferably, the control and computation unit 25 in conjunction with the metering and movement detection unit 21
25 responds to changes in colour or brightness of the selected areas so that if an object moves into shadow or illumination of a different colour temperature, the operator is alerted

or the correction factors automatically cancelled.

It is also possible to provide different correction factors for the same object (selected area) in different positions. The memory 26 may store the correction factors
5 and positions so that when the object moves between those approximate positions, the correction factors may be changed in turn with interpolation at the intervening positions. Ideally, the interpolation is responsive to the detected colours and brightness of the selected areas, such that a
10 correction factor is changed as the colour/brightness of a selected area changes.

Although movement of objects within the image may be detected electronically, for instance by means of edge detection, it is also possible to detect movement of the
15 camera and use this information to provide information regarding movement of objects as viewed by the camera. For example, transducers may be provided to detect tilting and panning of the camera and also to detect zooming of its lenses. The output of such transducers can then be used to
20 predict how the filmed image will change.

CLAIMS

1. A method of filming with a video camera having
an imaging device for producing video image data
5 representing the video image and a video amplifier stage the
method comprising:
adjusting the brightness and/or colour of at
least one selected area of the video image by processing the
video image data prior to its processing by the video
10 amplifier stage of the video camera.
2. A method according to claim 1, comprising
accounting for variations in colour and/or brightness
between different areas of the video image by selecting an
area and applying said processing to the selected area.
- 15 3. A video apparatus comprising:
a video camera having an imaging device for
producing video image data representing a video image;
selection means for enabling an operator to
designate a selected area of the video image and enter
20 information regarding the brightness and/or colour of the
selected area;
processing means connected to the imaging device
and the selection means for processing the video image data
of the selected area so as to adjust the brightness and/or
25 colour of the selected area according to the entered
information; and
a video amplifier and processor connected to the

output of the processing means.

4. A video camera device for use with a video camera, having an imaging device for producing video image data representing a video image and having a video amplifier
5 and processor, the device being adapted for insertion into the amplifier and being arranged for connection to the output of the imaging device and the input of the video amplifier and processor, the device comprising:

processing means for processing video image data
10 of a selected area of the video image so as to adjust the brightness and/or colour of the selected area.

5. A video apparatus comprising:
a video camera with an imaging device for producing video image data and a video amplifier and
15 processor;
a video camera device according to claim 4; and
selection means for enabling an operator to select an area of a video image and enter information regarding the brightness and colour of the selected area.

- 20 6. An apparatus according to claim 3 or 5 further comprising a display device for displaying video image data output by the video amplifier and processor, the selection means being arranged to enable an operator to select an area of the video image by indicating the area on the display
25 device.

7. An apparatus according to claim 6 wherein the selection means comprises at least one of a plurality of

keys, a joystick, and a pointing device such as a track ball or mouse for controlling an on-screen-cursor displayed on the display device.

8. An apparatus according to claim 6 or 7 wherein
5 the selection means comprises means for searching for brightness and/or colour transitions in the vicinity of the boundary of the selected area by analysing video image data output from the imaging device and means for redefining the selected area as being bounded by the transitions.

10 9. An apparatus according to any one of claims 3 and 5 to 8 further comprising means for measuring the brightness and/or colour temperature of the selected areas.

10. An apparatus according to any one of claims 3 and 5 to 9 wherein the processing means is operative to
15 calculate, in response to the entered information for each respective selected area, correction parameters for adjusting the brightness and/or colour of pixels in the respective selected area.

11. An apparatus according to claim 10 further
20 comprising a memory for storing the correction parameters of respective selected areas.

12. An apparatus according to any one of claims 3 and 5 to 11 further comprising movement detection means for detecting movement of selected areas between successive
25 frames.

13. An apparatus according to claim 12 when
appendant to claim 11 wherein the memory is arranged to

store, for each selected area, a plurality of correction parameters for a plurality of respective positions of the selected area within the video image and wherein the processing means is arranged to adjust the brightness and/or
5 colour of a selected area in accordance with the position of the selected area.

14. An apparatus constructed and arranged substantially as hereinbefore described with reference to Figures 3, 4 and 5 of the drawings.

10 15. A method of filming substantially as hereinbefore described with reference to and as illustrated by Figures 3, 4 and 5 of the accompanying drawings.



Application No: GB 9603415.2
Claims searched: All

Examiner: Joe McCann
Date of search: 18 April 1996

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK CI (Ed.O): H4F(FGB,FGC,FGT,FHL,FHM,FHHX)

Int CI (Ed.6): H04N(5/243,9/64,9/68,9/77)

Other: Online: WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
X	GB 2121645 (DAINIPPON SCREEN MFG) - see abstract and figure 2	1,3,4
X	WO 87/06419 (CORPORATE COMMUNICATIONS CONSULTANTS) - see abstract and figure 1	1,3,4
X	US 4803548 (KIRK) - see abstract	1,3,4

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.

& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.

E Patent document published on or after, but with priority date earlier than, the filing date of this application.